

Raindance Rainmaker

Overhead shower 600 3jet with lighting set

Surfaces: **Chrome** Article Number: **28404000**



Description

product features

- consists of: overhead shower, shower thermostat
- shower head size: 600 mm
- flow rate RainAir spray (at 0.3 MPa): 20 l/min
- flow rate RainAir XL (at 0.3 MPa): 26 l/min
- flow rate WhirlAir spray (at 0.3 MPa): 21 l/min
- the 3 spray zones must be controlled via 3 valves or a diverter valve with 3 outlets
- material spray disc: metal
- installation: flush with the ceiling
- connection dimension: DN20
- with integrated lighting
- illuminant: LED
- power supply: 12 V - DC
- transformer power supply for concealed installation 12 V, 18 W
- input voltage: 100 - 240 V AC / 50 / 60 Hz
- output voltage: 12 V - DC
- colour temperature: 2700 K
- energy efficiency label: C
- TÜV certified

Technology




Design awards




Certificates



Product image



Scale drawing




Raindance Rainmaker

Overhead shower 600 3jet with lighting set

Surfaces: **Chrome** Article Number: **28404000**



Flowchart



The consumption was measured in combination with the appropriate fittings (thermostat/mixer/in-wall valve) to reflect actual application in practice.